



Features

Model ACB-AS is a Multi-Heat Sensor, which is fully compatible with Hochiki's GTP Analogue Addressable Protocol. The ACB-AS incorporates a Variable Temperature heat element and a Rate Of Rise heat element, both of which are controlled from the Control Panel, allowing the selection of Type A, B, C or D.

User selectable modes
Incorporates Fixed Temperature and Rate Of Rise Heat elements
Twin fire LED's allow 360° viewing
Electronically Addressed
CSIRO Activfire Listed afp-1817

SPECIFICATION

Ordering Code	ACB-AS
Operating Voltage	17-31Vd.c. (Allowable Max 41Vd.c.)
Low Power Mode (typ)	110 μ A
Quiescent Current (typ)	350 μ A
Alarm Current (controlled by CIE)	19mA
Transmission Method	Digital Communications Using GTP
Operating Temperature Range	-10°C to + 80°C
Storage Temperature Range	-20°C to + 60°C
Maximum Humidity	95%RH – Non Condensing (at 40°C)
Colour/Case Material	Ivory White/Polycarbonate
Weight (g)	100
Diameter (mm) / Height with base (mm)	100 / 46
Compatible Bases	YBN-R/2NA, YBO-BS, YBO-R/SCI
Base Fixing Centres (mm)	48 ~ 74