

ESP intelligent ATJ-ASN-BLK

Analogue Multi-Heat Sensor

Features

- ▶ User selectable modes
- ▶ Incorporates Fixed Temperature and Rate of Rise Heat elements
- ▶ Twin LEDs allow 360° viewing – green when polling, turn red in fire
- ▶ Pulsing/non-pulsing controlled from panel*
- ▶ Electronically addressed
- ▶ Activfire (CSIRO) approved to AS7240.5
- ▶ SIL Level 2 approved variants available.



Description

Model ATJ-ASN-BLK is a Multi-Heat Sensor, which is fully compatible with Hochiki's ESP Analogue Addressable Protocol.

The ATJ-ASN-BLK incorporates a Variable Temperature heat element and a Rate of Rise heat element, both of which are controlled from the Control Panel, allowing either thermal element or both elements simultaneously to be active in making the fire decision. The sensor polling LEDs can also be controlled via the Control Panel (pulsing/non-pulsing)*.

Specification

Operating Voltage	17 – 41 VDC
Low Power Mode (typ)	110 µA
Quiescent Current (typ)	350 µA
Alarm Current (controlled by CIE)	9.1 mA (excluding remote indicator)
Transmission Method	Digital Communications Using ESP
Operating Temperature Range	-10 °C to + 50 °C
Operating Humidity	95% RH - Non Condensing (at 40 °C)
Storage Temperature Range	-30 °C to +60 °C
Storage Humidity	<80% RH at 70 °C
Colour / Case Material	White / Polycarbonate - ABS
Weight (g)	90
Diameter (mm) / Height (mm)	100 / 45
Base Fixing Centres (mm)	48 ~ 74
Compatible Bases*	YBN-R/3(BLK)
Approvals	AS7240.5 - Classes A1R, BR, CR, A1S, BS & CS
IP Rating	BS EN 60529:1992+A2 2013 (Protection rating IP42)
Compatible Panels	Kentec Electronics Ltd / Model : Syncro AS, & Taktis series FDCIE

*Control Panel compatibility required

Ordering Codes

Product

Analogue Multi-Heat Sensor (BLK Case)

Part Number

ATJ-ASN-BLK

Listings / Approvals

