

## CHQ-BACKBOX



### Product Overview

The **CHQ-Backbox** is designed for installations where the CHQ range of modules - CHQ-DIM(SCI), CHQ-SZM(SCI), CHQ-DZM(SCI), CHQ-DSC(SCI), CHQ-MRC(SCI), CHQ-DRC(SCI) and CHQ-PCM - require mounting within a glanded enclosure.

### Standard Features

- Provides glanded cable connections
- Robust design
- Compatible With All CHQ Modules

## SBB-1



### Product Overview

**Splashproof Base Backbox.** Provides an aesthetically pleasing solution where surface fixed devices are required. The housing supports four 20mm glanded entries for cabling access.

### Standard Features

- 4 glanded cable entry holes (glands not supplied)
- Colour matched
- Approved detector and base range
- Provides moisture and dust resistant fitting
- Ideal for bulkhead fitting
- Suitable for marine use

## YBO-BS-COV(W)



### Product Overview

**Protective Cap.** A protective cap which can be fitted to the YBO-R/SCI(WHT) isolator base, YBO-BS(WHT) or YBO-BSB(WHT) sounder bases when these devices are being used without a detector fitted.

### Standard Features

- Protects wiring terminals on isolator bases and base sounders
- Easy to fit
- Available in ivory or white

## SMB-1



### Product Overview

An **IP66 rated, grey (RAL7035) enclosure** designed for use with the Hochiki range of Modules. Supplied with a transparent black lid as standard. Used in conjunction with the SMB-ADAPTOR this enclosure can house any of the PCB assemblies from the Hochiki Smart-Fix module range

### Standard Features

- Quick-release screws
- Polyurethane gasket provides IP66 protection
- Corrosion free, resistant to most alkaline and acid
- Temperature resistance to +70°C, Impact resistant, and Nonflammable
- 32 knock-outs
- \* Dimensions L 254 x W 180 x H 90