

Product Overview

A Photoelectric Smoke Sensor incorporating Hochiki's unique High Performance Chamber which allows the sensor threshold level to be increased, thereby improving the signal to noise ratio and reducing susceptibility to false alarms.

Standard Features

- High Performance chamber
- Twin fire LEDs allow 360° viewing
- Locking mechanism (sensor to base)
- Variable sensitivity
- Electronically addressed
- Compatible bases: YBN-R/2NA, YBO-BS, YBO-BSB, YBO-R/SCI
- Approval: AS7240.7

ALK-AS



Product Overview

A Multi-Sensor incorporating a thermal element and a High Performance photoelectric smoke chamber.

Standard Features

- High Performance chamber
- Incorporates Optical & Heat elements
- Twin fire LEDs allow 360° viewing
- Variable sensitivity
- Electronically Addressed via the TCH-B200 handheld programmer
- Compatible bases: YBN-R/2NA, YBO-BS, YBO-BSB, YBO-R/SCI
- Approval: AS1603.1 & AS1603.2

ACA-E



Product Overview

A Multi-Heat Sensor incorporating a variable Fixed Temperature heat element and a Rate Of Rise heat element, both controlled from the Control Panel allowing either thermal element or both elements simultaneously to be active in making the fire decision.

Standard Features

- User selectable modes
- Incorporates Fixed Temperature and Rate Of Rise Heat elements
- Twin fire LEDs allow 360° viewing
- Electronically Addressed
- Compatible bases: YBN-R/2NA, YBO-BS, YBO-BSB, YBO-R/SCI
- Approval: AS1603.1. Type A, B, C and D

ACB-AS



Product Overview

An IP67 Rated Waterproof Multi-Heat Sensor which can be used externally and is supplied with its own fixing base which is used to fix the sensor. Flying leads from the sensor connect directly to the loop via waterproof connectors (Not supplied).

Standard Features

- User selectable modes
- Incorporates Fixed Temperature and Rate Of Rise Heat elements
- Twin fire LEDs allow 360° viewing
- Electronically addressed
- IP67 rated
- Supplied with fixing base
- Approval: AS1603.1 Type A, B, C and D

ACB-ASW



Product Overview

A Common Mounting Base which is fully compatible with ALK-ASN, ACA-ASN and ACB-ASN sensors. Supplied with square cable clamps for secure and reliable cable termination and is also capable of driving a remote LED if required.

(Red version – YBO-R/3(RED) for use with CHQ-WS2 Wall Sounder and CHQ-WSB Wall Sounder Beacon)

Standard Features

- Electronics free / Stainless steel contacts
- Takes 2.5mm² cables
- Slim profile – only 8mm
- Rugged wiring contacts
- Facility for remote indicator
- Quick connection via square cable clamps
- Available in RED for use with CHQ-WS2 Wall Sounder and CHQ-WSB Wall Sounder Beacon

YBN-R/2NA

