

YBN-R/3(WHT)
YBN-R/3(RED)
YBN-R/3(BLK)



Product Overview


A Common Mounting Base which is fully compatible with ALK-ASN, ACA-ASN and ACB-ASN sensors. Supplied with square cable clamps for secure and reliable cable termination and is also capable of driving a remote LED if required.

(Red version – YBO-R/3(RED) for use with CHQ-WS2 Wall Sounder and CHQ-WSB Wall Sounder Beacon)

Standard Features

- Electronics free
- Stainless steel contacts
- Takes 2.5mm 4 cables
- Slim profile – only 8mm
- Rugged wiring contacts
- Facility for remote indicator
- Quick connection via square cable clamps
- Available in RED for use with CHQ-WS2 Wall Sounder and CHQ-WSB Wall Sounder Beacon

YBN-R/3(WHT)-SCI **Product Overview**



Model YBN-R/3(SCI) is a sensor mounting base featuring an integral short-circuit isolator which will detect and isolate short-circuits on the loop. When a short-circuit is detected during power up the unit will drop the power to the rest of the loop. The YBN-R/3(WHT)-SCI is compatible with Hochiki Analogue sensors, beacons, sounders and indicators and does not require a loop address. A remote fire LED facility is provided when a sensor is attached to the base.

NOTE: A fitted sensor will still be powered when this device is isolating.

Standard Features

- Features integral SCI
- Easy to fit
- Slim profile
- Matches standard base colours

CHQ-WS2



Product Overview

An Addressable Loop-Powered Wall Sounder providing 8 volume levels and 51 tones with a maximum output of up to 102 dB(A) (± 2 dB(A)) with low current consumption.

Special bases available: YBO-R/3(RED), YBO-R/SCI(RED), YBO-R/3(WHT) and YBO-R/SCI(WHT-SNDR).

Standard Features

- Loop powered
- Single loop address – addressed via the TCH-B200 hand held programmer
- Variable sound output 90 ~ 102 dB(A) (± 2 dB(A)) output at 1m
- Fits Hochiki standard or isolator base
- Weatherproof kit available
- 51 User-selectable tones (all tones EN54-3 compatible)
- Auto-shutdown mode available*
- * Please ensure control panel compatibility

CHQ-WSB



Product Overview

An Addressable Loop-Powered Wall Sounder Beacon as per the CHQ-WS2 but additionally featuring an integral beacon within the horn which utilises high intensity LED technology.

Special bases available: YBO-R/3(RED), YBO-R/SCI(RED), YBO-R/3(WHT) and YBO-R/SCI(WHT-SNDR).

Standard Features

- As per CHQ-WS2 plus:
- Variable flash frequency*
- High intensity LED technology
- Independent control of sounder and beacon*
- Auto-shutdown mode available – can be set independently for sounder or beacon*
- * Please ensure control panel compatibility