

YBO-BS



Features

- * Loop Powered with Single Loop Address - addressed automatically by Control Panel or via the TCH-B100 Hand Held Programmer
- * Variable Sound Output 50 ~ 98 dB(A) (± 2 dB(A)) output at 1 metre*
- * Fits Hochiki Standard or Isolator Base and supports ESP Sensors, Addressable Beacons and Addressable Remote Indicator
- * 51 User-Selectable Tones (all tones EN54-3 compatible)
- * Auto-Shutdown feature prevents noise-pollution
- * Approved by LPCB & VdS
- * Also available in white
- * SIL Level 2 approved variants available

Description

Model YBO-BS is an addressable loop powered Base Sounder innovatively designed to give a range of tones and volumes with a maximum output of up to 98 dB(A) (± 2 dB(A)) with low current consumption. The unit is designed to fit to the Standard Base (YBN-R/3) or the Isolator Base (YBO-R/SCI – from Batch Number 6044) and can be fitted with any of the ESP Range of Sensors, Beacons or Remote Indicators. The unit can also be converted into a wall sounder with the simple addition of a Cap (SI/CAP). The sounder is Ingress Protection rated to IP21 and for internal use only. An Auto-Shutdown feature allows the user to set a fixed time within which the sounder will operate, before automatically silencing itself, cutting noise pollution.

Specification	
Ordering Codes	YBO-BS / YBO-BS(WHT) SI/CAP
Operating Voltage	17 ~ 41 VDC
Low Power Mode (typ)	40 μ A
Quiescent Current (typ)	150 μ A
Sounding Current (typ)	0.8 mA (50 dB(A) @ 1 m) ~ 16 mA (98 dB(A) @ 1 m)
Sound Output (at 1 metre)	50 ~ 98 dB(A) (± 2 dB(A)) @ 24 VDC or above (EN54-3 compliant)
Number of Tones	51
Tone Frequency Range	300 Hz ~ 2850 Hz
Operating Temperature Range	-10 °C to +50 °C
Storage Temperature Range	-30 °C to +70 °C
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Colour / Case Material	Ivory or white / PC+PS+GF5
Ingress Protection Rating	IP21
Weight (g) / Dimensions (mm)	112 / H113 x W113 x D43
Base Fixing Centres (mm)	48 ~ 74