incite fire

100mm (4") 100V 5W Ceiling Speaker

- Designed to meet Australian Standard AS 7240.24
- Excellent speech intelligibility
- Tuned PA driver designed to meet the latest fire standards
- High quality speaker driver developed for BGM, paging and emergency warning applications
- Fitted with 4 way wire protect terminal for loop in, loop out wiring.
- Fitted with cable restraint plate and flame retardent safety cover.
- 5 year warranty.

SP-C2170 (WHT)
SP-C2171 (BLK)

100mm One-Shot Rat-Trap EWIS Fire Ceiling Speakers with Plastic or Aluminium Grille

- Designed to meet Australian Standard AS 7240.24
- Excellent speech intelligibility
- Tuned PA driver designed to meet the latest fire standards
- High quality speaker driver developed for BGM, paging and emergency warning applications
- Fitted with 4 way wire protect terminal for loop in, loop out wiring.
- Fitted with cable restraint plate and flame retardent safety cover.
- 5 year warranty.

SP-CF2160 (WHT, P)
SP-CF2161 (BLK, P)
SP-CF2260 (WHT, A)
SP-CF2261 (BLK, A)

10W 100V Line ABS AS 7240.24 Horn Speaker

- Designed to meet AS 7240.24 for fire/evac installations
- Twist lock cap reduces installation time
- UV stabilised ABS construction
- Excellent sound dispersion
- IP66 rated for weather resisitance
- EWIS line monitoring system compatible
- Two cable glands supplied for loop in, loop out wiring
- 5 year warranty

HORN-CF2053G
HORN-CF2053R
HORN-CF2053W
HORN-CF2053B

100mm / 200mm 100V 5W Surface Mount Speaker

- Designed to meet AS ISO7240.24 standard for fire & evacuation warning systems
- Excellent speech intelligibility
- Fitted with supervisory capacitor for line monitoring
- High impact enclosure and grille

SPSM-CF0703 100mm (WHT)
SPSM-CF0704 100mm (BLK)
SPSM-CF0715 200mm (WHT)
SPSM-CF0716 200mm (BLK)

200mm 15W 100V Fire Speaker White

- Designed to meet AS ISO7240.24 standard for fire & evacuation warning systems
- Flame retardent housing
- Tuned PA driver to suit new approval requirements
- One-shot simple snap fit design

SPSM-CF0720