


## DIN Module Enclosure SMB-3



### Features

- \* Designed to house up to 4 Hochiki DIN Modules
- \* Quick-release screws
- \* Polyurethane gasket provides IP66 protection
- \* Corrosion free, resistant to most alkaline and acid
- \* Temperature resistance to +70°C, Impact resistant, and Non-flammable
- \* 20 knock-outs
- \* Supplied with DIN Rail and fixings

### Description

Model SMB-3 is from a range of IP66 rated, grey (RAL7035) enclosures, designed for use with the Hochiki range of DIN Modules. The SMB-3 features a selection of metric knockouts and is supplied with a transparent black lid as standard; an opaque lid is also available (sold separately).

The unit is supplied with a DIN Rail section (plus fixings) and will accept up to four Hochiki DIN Rail Modules, side-by-side.

Specification		
Ordering codes	SMB-3 Base c/w transparent lid	SMB-3(LID) Opaque lid
Ingress Protection rating	IP66	N/A
Colour	Box - Grey (RAL7035) Lid - Transparent black	Grey (RAL7035)
Material	Box - Polystyrene Lid - Polycarbonate	Polystyrene
Weight (g)	575	300
Dimensions (mm)	L180 x W110 x H165	L180 x W110 x H92
DIN Rail dimensions (mm)	L100 x W35 ('top hat')	N/A
Knock-out configuration	Long sides	1 x M32/40 4 x M20
	Short sides	1 x M20/25 4 x M20
Suitable protection against	Weak alkali, strong alkali, alcohol, petrol, benzene, mineral oil, diesel, ammonia, vegetable oil, animal oil	