

Data Sheet

CA-FC7402-LD-100

CA-FC7402-LD-200

CA-FC7402-LD-500

CA-FC7502-LD-100

CA-FC7502-LD-200

CA-FC7502-LD-500



Product Overview

Fire Control - Light Duty

- Application:** These Light duty Fire Control Cables are suitable for Fire Alarms, Smoke Detectors, Speakers, Modules, Evacuations Systems, 24VDC Power & Ancillaries
- Conductor:** Plain Annealed Copper
- Insulation:** PVC V75 or low Smoke Zero Halogen
- Sheath:** PVC V75 or low Smoke Zero Halogen
- Sheath Colour:** Red (Optional Red or Yellow Trace/Stripes)
- Standards:** AS/NZS 3013:2005 (WSX1 - Mechanical), AS/NZS 1125, IEC 60228, AS/NZS 3808, AS/NZS 5000.2, AS 1670:2018 ELV Markings, AS/ACIF S008 ACMA Compliance
- Greenstar:** Approved

Flat Red Twin TPS								
Part No	Size (mm ²)	Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Sheath Colour/s	O.D. (mm)	Marking	Drum Size (m)
CA-FC7402-LD-100	0.75	2	0.6	0.9	Red	4.1 x 6.4	ELV Fire	100
CA-FC7402-LD-200	0.75	2	0.6	0.9	Red	4.1 x 6.4	ELV Fire	200
CA-FC7402-LD-500	0.75	2	0.6	0.9	Red	4.1 x 6.4	ELV Fire	500
CA-FC7502-LD-100	1.5	2	0.6	1.1	Red	4.9 x 7.5	ELV Fire	100
CA-FC7502-LD-200	1.5	2	0.6	1.1	Red	4.9 x 7.5	ELV Fire	200
CA-FC7502-LD-500	1.5	2	0.6	1.1	Red	4.9 x 7.5	ELV Fire	500