

Data Sheet

CA-FC7402-LDT-100

CA-FC7502-LDT-200

CA-FC7502-LDT-500



Product Overview

Fire Control - Light Duty

- Application:** These Light duty Fire Control Cables are for Addressable Detector Loops
- Conductor:** Plain Annealed Copper
- Insulation:** PVC V75 or low Smoke Zero Halogen
- Sheath:** PVC V75 or low Smoke Zero Halogen
- Sheath Colour:** Red
- Standards:** AS/NZS 3013:2005 (WSX1 - Mechanical), AS/NZS 1125, IEC 60228, AS/NZS 3808, AS/NZS 5000.2, AS 1670:2018 ELV Markings, AS/ACIF S008 ACMA Compliance
- Greenstar:** Approved

Twisted Red Twin TPS								
Part No	Size (mm ²)	Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Sheath Colour/s	O.D. (mm)	Marking	Drum Size (m)
CA-FC7402-LDT-100	0.75	2	0.6	0.8	Red	6.9	ELV Fire	100
CA-FC7502-LDT-200	1.5	2	0.7	0.8	Red	8.4	ELV Fire	200
CA-FC7502-LDT-500	1.5	2	0.7	0.8	Red	8.4	ELV Fire	500