



CABLE

CA-FRC2015-XXX* Fire Rated Multicore 1.5mm² - 2 Core (No Earth)

Flexible multi-core halogen free, low smoke, low toxicity, non-corrosive emission, flame retardant cables for fire detection, control, warden intercom phones & 1668 smoke controls. Available in drum of 100m, 250m & 500m. The fire rated multicore cable has a plain annealed copper conductors and a mica glass tape barrier.

General Data

- Conductor: Plain annealed copper
- Conductor area: 1.5mm² per core
- Insulation: X-HF-110
- Core colours: White & Red
- Sheath colour: Red
- Sheath: HFS-110-TP
- Voltage: 450/750V
- Standards: AS/NZS 3013:2005 - Category WS52W, IEC 60332-3 and BS6387
- Greenstar: Approved
- Drum size: Various
- Insulation thickness: 0.6mm
- Sheath thickness: 1.3mm
- Outside diameter: 10.3mm +/- 10%
- Min. bend radius: 210mm
- Marking: ELV Fire

Ordering Information*

- 100m drum: CA-FRC2015-100
- 250m drum: CA-FRC2015-250
- 500m drum: CA-FRC2015-500

Scope of Delivery

- 1 x CA-FRC2015-100 - cable drum + 100m cable
- 1 x CA-FRC2015-250 - cable drum + 250m cable
- 1 x CA-FRC2015-500 - cable drum + 500m cable

CABLE