



CABLE

CA-FRC2075-XXX* Fire Rated Multicore 0.75mm² - 2 Core (No Earth)

Flexible multi-core halogen free, low smoke, low toxicity, non-corrosive emission, flame retardant cables. Available in drum of 100m, 250m & 500m. The fire rated multicore cable has a plain annealed copper conductors and a mica glass tape barrier.

General Data

- Conductor: Plain annealed copper
- Conductor area: 0.75mm² per core
- Insulation: X-HF-110
- Core colours: White & Red
- Sheath colour: Red
- Sheath: HFS-110-TP
- Voltage: 450/750V
- Greenstar: Approved
- Drum size: Various
- Insulation thickness: 0.6mm
- Sheath thickness: 1.2mm
- Outside diameter: 9.4mm +/- 10%
- Min. bend radius: 190mm
- Marking: ELV Fire

Ordering Information*

- 100m drum: CA-FRC2075-100
- 250m drum: CA-FRC2075-250
- 500m drum: CA-FRC2075-500

Scope of Delivery

- 1 x CA-FRC2075-100 - cable drum + 100m cable
- 1 x CA-FRC2075-250 - cable drum + 250m cable
- 1 x CA-FRC2075-500 - cable drum + 500m cable

CABLE

All specifications and other information shown were current as of document revision date and are subject to change without notice. Ver 1.01 08/2024