

Data Sheet

CA-FREAS7501P-100R

CA-FREAS7501P-250R

CA-FREAS7501P-500R



Product Overview

Fire Rated Cable - Overall Screened

- Application:** Screened 2 core cable for networking and data
Conductor: Plain Annealed Copper
Voltage: 450/750V
Barrier: Mica Glass Tape (WS52W)
Insulation: X-HF-110
Screen: Aluminium tape screen, polyester mylar tape lapping and, 7/0.25mm copper drain wire
Sheath: HFS-110-TP
Sheath Colour: Red
Core Colours: White and Black numbered cores
Standards: AS/NZS 3013:2005, AS/NZS 3191, AS/NZS 1125
Greenstar: Approved
Pack Lengths: 100m, 250m, and 500m

Fire Rated Screened Red Twin									
Part No	Size (mm ²)	Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Sheath Colour/s	O.D. (mm)			Drum Size (m)
CA-FREAS7501P-100R	1.5	2	0.4	0.8	Red	8.4			100
CA-FREAS7501P-250R	1.5	2	0.4	0.8	Red	8.4			250
CA-FREAS7501P-500R	1.5	2	0.4	0.8	Red	8.4			500