

## Data Sheet

CA-XFRC2015-W100

CA-XFRC2015-W250

CA-XFRC2015-W500



## Product Overview

### Fire Rated Cable

**Application:** Multi-core halogen free, low smoke, low toxicity, non-corrosive emission, flame retardant cables for 70V & 100V evacuation speakers

**Conductor:** Plain Annealed Copper (Class 2 of IEC60228)

**Barrier:** Mica Glass Tape

**Insulation:** X-HF-110

**Sheath:** HFS-110-TP, Flame Retardant

**Sheath Colour:** Red or Red c/w white Stripe (Trace)

**Standards:** AS/NZS 3013:2005 - Category WS52W, IEC 60332-3, BS6387

**Greenstar:** Approved

Fire Rated Red/White Stripe Twin									
Part No	Size (mm <sup>2</sup> )	Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Sheath Colour/s	O.D. (mm)	Marking	Minimum Bend Radius (mm)	Drum Size (m)
CA-XFRC2015-W100	1.5	2	0.6	1.3	Red/White Stripe	10.3	LV Fire	210	100
CA-XFRC2015-W250	1.5	2	0.6	1.3	Red/White Stripe	10.3	LV Fire	210	250
CA-XFRC2015-W500	1.5	2	0.6	1.3	Red/White Stripe	10.3	LV Fire	210	500