

# MARINE DCD-CE3M

Your Safety, Our Technology

Marine Approved Conventional Combined Rate of Rise & Fixed Temperature Heat Detector (90°C)

## Features

- ▶ Electronic linear heat detection
- ▶ Remote indicator output
- ▶ Wide voltage range (9.5 ~ 30 V dc)
- ▶ Twin fire LEDs allow 360° viewing
- ▶ Approved by LPCB and GL



## Description

Model DCD-CE3M is a Marine Approved Rate of Rise Heat Detector with a 90°C fixed temperature element using a thermistor and linearising circuit to provide an accurate linear response Heat Detector.

The DCD-CE3M is ideal for use where medium ambient temperatures exist, such as drying rooms or where Smoke Detectors are unsuitable because of the presence of steam or cooking fumes such as in a kitchen/galley.

The DCD-CE3M is supported on the majority of conventional systems. A third terminal provides remote indicator output.

## Specification

Ordering Code	DCD-CE3M
Operating Voltage	9.5 – 30 V dc
Quiescent Current (typ)	35 $\mu$ A
Maximum Current in Alarm (typ)	40 mA
Remote Indicator Drive	20 mA (max) / 9.5-14 mA (typ)
Operating Temperature Range	-10 $^{\circ}$ C to +50 $^{\circ}$ C
Storage Temperature Range	-30 $^{\circ}$ C to +70 $^{\circ}$ C
Maximum Humidity	95% RH - Non Condensing (at 40 $^{\circ}$ C)
Ingress Protection Rating	IP63
Colour / Case Material	Ivory or White / Polycarbonate
Weight (g) / Diameter (mm) / Height (mm)	76 / 100 / 38
Compatible Base	YBN-R/6M
Base Fixing Centres (mm)	48 ~ 74
Approvals to (EN54:2000) Class A1 & A1R	LPCB & GL

## Ordering Codes

### Product

Intrinsically Safe Conventional Rate of Rise Heat Detector

Intrinsically Safe Conventional Rate of Rise Heat Detector (White)

### Part Number

DCD-CE3M

DCD-CE3M(WHT)

## Approvals

