

# Hochiki Conventional
## IP67 Weatherproof Fixed Temperature Heat Detector (60° C)

DFV-AWK-A-OW

## Features

- Electronic linear heat detection
- Remote indicator output
- Wide voltage range (9.5 ~ 30 VDC)
- Twin fire LEDs allow 360° viewing
- IP67 Ingress protection
- Activfire Certified to AS7240.5 - Class A2

## Description

Hochiki Model DFV-AWK-A-OW is a Conventional A2 Class, IP67 Rated Weatherproof 60ºC fixed temperature Heat Detector using a thermistor and linearising circuit to provide an accurate linear response.

The DFV-AWK-A-OW is suited to outdoor / harsh environments, where exposure to high levels of condensation or water exist.

The DFV-AWK-A-OW has a wide voltage range and requires no mounting base as short sealed fly leads are provided for connection to the conventional zone and remote LED output where required.

## General Data

| | |
|---|---|
| Operating voltage: | 9.5 - 30 VDC |
| Quiescent current (typ): | 17uA @ 24 VDC |
| Maximum alarm current (typ): | 80 mA |
| Remote indicator drive: | 20 mA (max) / 9.5-14 mA (typ) |
| Operating temperature: | -10ºC to +50ºC |
| Operating humidity: | 95% RH - non condensing (at 40ºC) |
| Storage Temperature: | -30ºC to +70ºC |
| IP rating: | IP67 |
| Colour / Case material: | White / Polycarbonate |
| Weight: | 76g |
| Diameter / Height: | 100mm / 38mm |
| Compatible bases (white): | N/A |
| Base fixing centres (mm): | 48 - 74mm |
| Approvals: | AS7240.5 - Class A2 |
| Activfire Certificate No: | afp-4004 |

## Ordering Information

| | |
|---|---|
| White model: | DFV-AWK-A-OW |

## Scope of Delivery

- Each (1)
- Box qty = 10
- Carton qty = 100

All specifications and other information shown were current as of document revision date and are subject to change without notice. Ver 1a.11.26



1300 INCITE
www.incitefire.com.au