

Product Overview

Our range of illuminated warning signs employ the very latest in LED technology to provide a high reliability, high brightness, audio/ visual warning indication unit. The brightness of the sign remains constant over its entire operating range of 15 to 30 volts DC due to the unique power boost circuitry employed. This ensures that even with a system running on depleted batteries, all signs remain at full intensity. A range of standard text signs are available and customised text and languages are easily accommodated due to the unique method employed to apply the lettering. The split level design allows one message to be displayed in the top half of the sign and an additional message to be displayed in the bottom half of the sign allowing for two stage warnings for systems such as extinguishing protection system.

RS485 Warning Signs - For Sigma XT Extinguishant Panel

ECU-WS-ESI



Product Overview

"EXTINGUISHING SYSTEM INOPERATIVE"

- High brightness white LED's
- Split level function - programmable
- Up to 7 signs per RS485 bus
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- **ECU-WS-ESI-WP (weatherproof)** 300W x 230H x 86D (mm)

ECU-WS-FA-DNE



Product Overview

"FIRE ALARM/DO NOT ENTER"

- High brightness white LED's
- Split level function - programmable
- Up to 7 signs per RS485 bus
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA

ECU-WS-FA-EVAC



Product Overview

"FIRE ALARM/EVACUATE AREA"

- High brightness white LED's
- Split level function - programmable
- Up to 7 signs per RS485 bus
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA
- **ECU-WS-FA/EVAC-WP (weatherproof)** 300W x 230H x 86D (mm)

ECU-WS-FA-DNE-WP



Product Overview

"FIRE ALARM/DO NOT ENTER"

(Weatherproof)

- High brightness white LED's
- Split level function - programmable
- Up to 7 signs per RS485 bus
- Internal buzzer with disable
- 300W x 230H x 86D (mm)
- 15-30VDC / 130mA / IP 55

Generic Warning Signs

WS-GEN-ESI



Product Overview

"EXTINGUISHING SYSTEM INOPERATIVE"

- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- **WS-GEN-ESI-WP (weatherproof)** • 300W x 230H x 86D (mm)

WS-GEN-FA-DNE



Product Overview

"FIRE ALARM/DO NOT ENTER"

- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA

WS-GEN-FA-EVAC



Product Overview

"FIRE ALARM/EVACUATE AREA"

- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA
- **WS-GEN-FA-EVAC-WP (weatherproof)** • 300W x 230H x 86D (mm)

WS-GEN-FA-DNE-WP



Product Overview

"FIRE ALARM/DO NOT ENTER"

(Weatherproof)

- IP 55
- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 230H x 86D (mm)
- 15-30VDC / 130mA /

(KM-FS-WS)



Flush Surround

Available for all non-weatherproof warning signs