

## 24M ADDRESSABLE EXIT SIGN



Ordering code	Straight – Single	EL-24S Kit
	Left – Single	EL-24L Kit
	Left – Double	EL-24LD Kit
	Right – Single	EL-24R Kit
	Right – Double	EL-24RD Kit
Kit Contents	Exit Sign Frame	EL-24-AS
	Reflective Worm backplate and rivets assy	EL-24G-AS
	Straight lens	EL-24G-S-AS
	Left lens	EL-24G-L-AS
	Right lens	EL-24G-R-AS
	Battery	EL-BAT450-AS (7.4v, 450mA, 3.33Wh)
	Compatible base	EL-TSB
Operating voltage	24v-40v	
Minimum standby operating Time	+ 3hours	
Power consumption from line(W)	1.1 Watt	
LED life time	+100,000Hrs	
Dimensions (mm) including base	Wall mounted	328L x 280H x 100D
	Ceiling mounted	328L x 290H x 100D
Weight including battery (g)	790	
Temp range	40°C	
Material	Cup and Bracket	Fire retardant
	Lens	Acrylic
Fire class	UL94 V-O	
IP rating	IP20 (IP44 option available)	
Case colour	White (RAL9003 "Signal White")	
Approval	AS2293, AS/NZ60598.2.22, EN55015	

An LED-based, addressable 24m viewable exit light with a flexible 'flex it' hinge solution. The exit light's hinge cup contains the electronics and stand-by battery and allows the unit to attach to the Hochiki EL-TSB mounting base. The cup also features a bicoloured status LED indicating charge/fault status (green for charging, red for fault), approved to AS2293.



**EL-24-AS**  
24m Emergency Exit Sign Frame, white (battery required)



**EL-24G-AS**  
24m Reflective Worm Back plate and Rivets Assy



**EL-24G-S-AS**  
FIREscape 24m Lens, STRAIGHT



**EL-24G-L-AS**  
FIREscape 24m Lens, LEFT arrow



**EL-24G-R-AS**  
FIREscape 24m Lens, RIGHT arrow