

EL-DL3-AS OPEN SPACE DOWN LIGHT



EL-DL3-AS is an LED-based, addressable open space down light featuring one high-powered LED with a specially engineered dual surface free-form optic. The unit's body contains the electronics and the stand-by battery and features a bicoloured status LED indicating charge/fault status (green for charging, red for fault).

The unit has been designed to easily fit onto Hochiki's base, the EL-TSB.

Ordering code	EL-DL3 Kit	
Kit Contents	Open Area Down light	EL-DL3-AS
	Battery	EL-BAT450-AS (7.4v, 450mA, 3.33Wh)
Compatible base	EL-TSB	
Operating voltage	24v-40v	
Minimum standby operating Time	+ 3hours	
Power consumption from line(W)	0.1 Watt	
LED life time	+100,000Hrs	
Dimensions (mm)	100(diameter) x 48(height) (inc 8mm for EL-TSB)	
Weight including battery (g)	100	
Temp range	40°C	
Case material	Fire resistant PC + ABS plastic (FR3010)	
Fire class	UL94 V-O	
IP rating	IP20 (IP67 option available)	
Case colour	White (RAL9003 " Signal White")	
Approval	AS2293, AS/NZ60598.2.22, EN55015	
Classification	C0:E6.3, C90:E6.3	