

## **HFTS2-FDSG**

## **STANDARD HFT Pipe**



## **Features**

- Environmentally friendly -Green Star Rated
- Suited for ASD Smoke Detection System
- Medium Duty (Black)
- Can be produced in any colour (subject to quantities)
- In accordance with AS/NZS 2053-UL 94-VO
- · High chemical resistance
- Operating temp -40°C to 110°C
- Suitable for outdoor use –
  Long term UV exposure

## **Description**

The plastic for use in the production of Halogen-free conduit contains no chlorines or heavy metals and thus offers decisive advantages over conventional systems.

- Provides significant environmental features compared to PVC
- No Corrosive or acidic gas formation in fire situations and no secondary damages to electronic equipment, machines and buildings
- No aggressive fumes which endanger the lives of humans and animals
- Available with or without "Air Sampling" markings
- Reduced smoke density, giving better visibility at fire exits & for rescue team

| Technical Specifications |                                     |  |  |  |
|--------------------------|-------------------------------------|--|--|--|
| Part code                | HFTS2                               |  |  |  |
| Length                   | 4 metre                             |  |  |  |
| Outside diameter         | 25mm                                |  |  |  |
| Inside diameter          | 21.4mm                              |  |  |  |
| Temperature Range        | -40°C to 110°C                      |  |  |  |
| Standard colour          | Black                               |  |  |  |
| Joining Adhesive         | HFTDP8010 solvent<br>(NOT PVC glue) |  |  |  |

Available with or without "Air Sampling" markings





| MATERIAL PROPERTIES                    | VALUE  | UNIT               | TEST METHOD        |
|--|--------|--------------------|--------------------|
| Density                                | 0.9    | g/cm³              | ASTM D792          |
| Flexural Modulus                       | 14,000 | kg/cm <sup>2</sup> | ASTM D790          |
| Elongation at Break                    | >500   | %                  | ASTM D638          |
| IZOD Impact Strength (Notched, 23°C)   | >50    | kg-cm/cm           | ASTM D256          |
| Rockwell Hardness                      | 85     | R Scale            | ASTM D785          |
| Tensile Strength at Yield              | 240    | kg/cm <sup>2</sup> | ASTM D638          |
| Halogen Content                        | 0      | %                  | Ion Chromatography |
| UV Resistance ( Black )                | >50    | years              |                    |
| UV Resistance ( Grey )                 | 5-10   | years              |                    |
| Thermal Conductivity at -20°C          | 0.24   | W/m K              |                    |
| Co-efficient of Thermal Expansion      | 0.15   | mm/m/°C            |                    |
|  |        |                    |                    |
| FIRE BEHAVIOUR                         |        |                    |                    |
| Flame Retardancy                       | VO     |                    | UL 94              |
| Flame Retardancy                       | 32     | %                  | L.O.I.             |
| Smoke Characteristics                  | 1-2    | Indice             | AS/NZS 1530.3:1999 |
|  |        |                    |                    |
| PERFORMANCE                            |        |                    |                    |
| Max. Working Temperature               | 105    | °C                 |                    |
| Min. Working Temperature               | -20    | °С                 |                    |
|  |        |                    |                    |
| JOINING METHOD                         |        |                    |                    |
| Adhesive                               | >2.3   | MPa                |                    |
|  |        |                    |                    |
| STANDARDS COMPLIANCE                   |        |                    |                    |
| AS / NZS 1345 "Content Identification" |        |                    |                    |
| AS / NZS 2053 "Conduits & Fittings"    |        |                    |                    |



| BS / EN 61386-21 " Conduit Systems"    |  |  |
|--|--|--|
| IEC 60423 "Conduit Systems"            |  |  |
| ISO9001:2008 Quality Management        |  |  |
| ISO14001:2004 Environmental Management |  |  |
|  |  |  |