



## Water retaining box

### SEC-WRB-25-PVC

### SEC-WRB-25-ABS

Water retaining box standard  
Used in rooms with high humidity.  
Inserted into the sampling pipe before  
DTB 25 PC (when used), any types of  
dust filters (when used) and SEC-ASD.

#### Technical data

Dimensions (H x W x D):	335 x 250 x 90 mm
Material:	PC
Pipe connection diameter:	25 mm



## Air cooler and water separator

### SEC-LK-35-PVC

### SEC-LK-35-ABS

Is used as an air cooler when the  
sampling pipe is in a room >60°C.  
Can also be used as a water separator  
in rooms with high amount of air  
humidity and / or condensing water  
because of temperature differences.  
For more details see the technical  
documentation.

#### Technical data

Dimensions (H x W x D):	1000 x 730 x 80 mm
Material:	Copper pipe d=22x1 mm
Weight:	8 Kg
VdS-Approval:	G208154
CPD-Approval:	0768-CPD-20600



## Detonation flame arrester

### SEC-DFA-25-3

Detonation flame arrester for explosion zones.  
Equipment category IIC. 2 pieces are needed  
per sampling tube. For more details see the  
technical documentation.

#### Technical data

Pipe connection diameter:	25 mm
---------------------------	-------



## Detonation flame arrester

### SEC-DFA-25-2

Same as DFA 25-3 but equipment category IIB.

#### Technical data

Pipe connection diameter:	25 mm
---------------------------	-------



## Detonation flame arrester

### SEC-DFA-25-1

Same as DFA 25-3 but equipment category IIA.

#### Technical data

Pipe connection diameter:	25 mm
---------------------------	-------



## Noise reduction housing

### SEC-Insulation-housing

The noise insulation housing is used as an  
accessory part for the aspirating smoke  
detector ASD 535 in areas where a low level  
of noise is required. If the ventilator noise  
from the aspirating smoke detector is found  
to be disruptive and changing the location of  
the evaluation unit is not possible, the  
aspirating smoke detector can be integrated  
into a noise insulation housing.

#### Technical data

Sound pressure level:	20 dB (A)
Dimensions (H x W x D) :	500 x 500 x 300 mm
Material:	Steel sheet
Weight :	21,5 kg
Protection class:	IP 54



## Additional housing for SecuriRAS SEC-ASD-535

### SEC-ASD-Housing-Ex

The additional housing is designed for the  
integration of an aspirating smoke detector  
SEC-ASD-535. The additional housing  
should be used as additional personal  
protection in explosive areas. If there is  
danger of operations related damage (e.g.  
lift truck operations) to the aspirating smoke  
detector, the additional housing can serve  
as a mechanical protection measure.

#### Technical data

Material:	Steel sheet
Dimensions (H x W x D):	500 x 500 x 300 mm
Weight:	21 kg
Protection class:	IP 54