

### SEC-ASD planning and calculation software

#### SEC-ASD-PipeFlow

Planning and calculation software for planning symmetric and asymmetric sampling pipe topologies. (Subject to licence)

#### Technical data (requirements)

Operating system:	Windows XP / 7 / 8.1
RAM:	1 GB
Hard disc space required:	50 MB



### SEC-ASD configuration tool license with USB Dongle

**SEC-D&PL\_ASD-Conf\_N** Dongle & Partner License ASD Config Networking



### SEC-ASD configuration tool license with USB Dongle

**SEC-D&PL\_ASD-Conf** Dongle & Partner License ASD Config



### USB 2.0 cable for connection between SEC-ASD-535 and PC

#### SEC-KAB-USB-45

USB 2.0 cable for connection between SEC-ASD-535 and PC for commissioning and maintenance via ASD Config

#### Technical data

Length:	4.5m
Type:	A-B

## SAMPLING POINTS



### Sampling hole clip

SEC-Clip x.x PA

**SEC-CLIP 2.0 PA**

**SEC-CLIP 2.5 PA**

**SEC-CLIP 3.0 PA**

**SEC-CLIP 3.5 PA**

**SEC-CLIP 4.0 PA**

**SEC-CLIP 4.5 PA**

**SEC-CLIP 5.0 PA**

**SEC-CLIP 5.5 PA**

**SEC-CLIP 6.0 PA**

**SEC-CLIP 6.5 PA**

**SEC-CLIP 7.0 PA**

\* Also available in white

Sampling hole on aspirating pipe (clip). Available with different diameter according to the project data.

Only for PVC and ABS pipes with 25 mm diameter  
Packaging unit: 10 pieces

#### Technical data

Hole diameter	Type
2.0 mm	SEC-CLIP 2.0 PA
2.5 mm	SEC-CLIP 2.5 PA
3.0 mm	SEC-CLIP 3.0 PA
3.5 mm	SEC-CLIP 3.5 PA
4.0 mm	SEC-CLIP 4.0 PA
4.5 mm	SEC-CLIP 4.5 PA
5.0 mm	SEC-CLIP 5.0 PA
5.5 mm	SEC-CLIP 5.5 PA
6.0 mm	SEC-CLIP 6.0 PA
6.5 mm	SEC-CLIP 6.5 PA
7.0 mm	SEC-CLIP 7.0 PA



### Maintenance clip

**SEC-Clip-REV PA**

Clip without hole for revision purpose.  
Packaging unit: 10 pieces

#### Technical data

Pipe connection:	25 mm
Material:	PA