



**Flexible Hose Polyamide 5/3mm**

**SEC-FH 5-3 PA 25**

Flexible Hose to connect the ADW detection unit with the sensor part (Cu, St, PTFE) of the sensing tube. (reel 25m). To be used together with stiffener sleeve SEC-SS 3 CuZn or SEC-SS 3 St.

*Technical data*

Diameter outside:	5 mm
Diameter inside:	3 mm
Length:	25 m
Material:	polyamide



**Stiffener sleeve brass for FH 5/3 PA**

**SEC-SS 3 CuZn**

Stiffener sleeve for SEC-FH 5-3 PA

*Technical data*

Material:	brass
Packaging unit:	10 pieces



**Stiffener sleeve stainless steel for FH 5/3 PA**

**SEC-SS 3 St**

Stiffener sleeve for FH 5/3 PA

*Technical data*

Material:	stainless steel
-----------	-----------------

## INSTALLATION MATERIAL



**Pipe clamp**

**SEC-PC 5-6 PA**

To mount the sensing tube.

*Technical data*

For pipe diameter:	5 mm
Temperature range:	-40 to +85°C
Material:	polyamide
Packaging unit:	100 pieces



**Pipe clamp**

**SEC-PC 5-6 St**

To mount the sensing tube.

*Technical data*

For pipe diameter:	5 mm
Material:	stainless steel
Packaging unit:	10 pieces



**Pipe clamp**

**SEC-PC 5-6 StG**

To mount the sensing tube. With brass stiffener. (delivery unit 10 Pipe clamps and 10 brass stiffener)

*Technical data*

For pipe diameter:	5 mm
Material:	brass
Packaging unit:	10 pieces



**ADW Sensing tube cleaning and maintenance set**

**SEC-ACMS 535**

ADW Sensing tube cleaning and maintenance set.