

## ROSHNI



## 9-28VDC ELECTRONIC SOUNDER

- High sound output
- Wide operating voltage 9-28Vdc
- Low current consumption
- 32 selectable tones
- Volume control

ROSHNI • Lockable shallow base standard & deep base available for IP65

## BEACON-R BEACON-A



## 24VDC RED (R)STROBE / (A) AMBER STROBE

- Wide operating voltage 9-60Vdc
- Current surge suppression
- High efficiency
- Constant performance over voltage range
- Locking base standard

BEACON-R • Deep base available for IP65

BEACON A = Amber strobe

## STR-LAB



## STROBE 'FIRE' LABEL TO SUIT BEACON-R

- Foam PVC label
- Complies to AS1670.1 2004
- Pre drilled to suit BEACON-R
- Red lettering on white background

## FLASHNI



## COMBINED SOUNDER STROBE

- Operating voltage 18-28Vdc
- High output sounder beacon
- Volume control
- Lockable base standard
- Deep base available for IP65

## SQUASHNI



## SOUNDER

- Fixing platform for Hochiki detector bases
  - Blank cover for use as stand alone sounder
  - Colour matched to Hochiki detectors
  - Operating voltage 10-28Vdc
  - Operating current 8-35mA
- SQUASHNI • Ultra slim profile for unobtrusive installation

## SQUASNIMICRO



## LOW CURRENT SOUNDER

- 100V line dual cone fire/evac speaker
- 5 tapings up to 5W
- Transformer safety cover
- Back box with concealed internal fixings
- Quick fit speaker snaps into back box

## STRRED-AMB-LP



## RED & AMBER STROBE SET ON METAL PLATE

- Low current draw 100mA
- Sturdy white powder coated steel chassis
- Simple bolt on installation
- Conduit knockouts for cable entry
- Operating voltage 24 dc
- Dimensions 285L x 122W x 85H • Flash rate 1.5Hz
- Terminal block enables 2,3 or 4 wire operation

## STRRED-AMB-WP



## WEATHERPROOF RED & AMBER STROBE SET

- No start up current surge
- Flash rate 60/min
- Operating voltage 20-30Vdc
- IP65 rating
- White ABS plastic base
- Dimension 185L x 93W x 100H
- Low current consumption - 90mA per strobe

## WIP-S



## RED WARDEN INTERCOM PHONE

- Separate speaker for call tone
- Selectable line impedance 600Ω or 4.7KΩ
- Simple two wire connection
- Includes wall mounting bracket
- Water & dust protected to IP65

## B8-24



## BELL 8"

- Red finish with 'FIRE' in large lettering.
- Back box available
- Dimensions: 200mm diameter /8 inches